


### Product Group MFCB

Articulated machine feet made of glass fibre reinforced polyamide with galvanized steel thread and antislip pad (A)




#### Standard Colours

- black

#### Material

- Thread: zinc-plated steel
- Base: glass fibre reinforced polyamide (PA-GF)
- Antislip pad: NBR 70 Shore



#### Product information

- There are two prepared screw-on holes (closed).
- The machine foot can compensate for uneven floors up to 30°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Packaging industry, conveyor systems, automation industry, office desks, aluminium profiles

#### Product options on inquiry

- Delivery with additional steel nut possible.

A	D	d	F max.	H	H1	M	WAF	50	100	150	200	250
mm	mm	mm	kg	mm	mm		mm	mm	mm	mm	mm	mm
54	83	8,5	1000	18	30	M10	7	x	x	x		
54	83	8,5	1300	18	30	M12	9	x	x	x		
54	83	8,5	1600	18	30	M16	13		x	x	x	
54	83	8,5	1800	18	32	M20	17		x	x	x	x
73	103	12,5	1800	20	32	M16	13		x	x	x	
73	103	12,5	2000	20	32	M20	17		x	x	x	x
73	103	12,5	2500	20	32	M24	20		x	x	x	x
87	123	12,5	1800	22	34	M16	13		x	x	x	
87	123	12,5	2000	22	36	M20	17		x	x	x	x
87	123	12,5	2500	22	36	M24	20		x	x	x	x
87	123	12,5	2500	22	36	M30	20		x			
87	123	12,5	2500	22	36	M30	26			x	x	x

#### Ordering example

- Group + D + M + Thread Length ---> MFCB 83 M16x 100 (A)