


Product Group MFK

Machine feet made of stainless steel with rubber base to cope slopes on the floor and equipment




Standard Colours

- white

Material

- Thread: AISI 304 (A2)
- Rubber: NBR 72 Shore



Product information

- The rounded design of this type makes cleaning easy.
- The rubber pressed into the foot plate meets the USDA standard for rubber products.
- The machine foot can compensate for uneven floors up to 20°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

| D | F max. | H | M | WAF | 50 | 70 | 100 | 150 | 180 | 230 | 310 |
|-----|--------|----|-----|-----|----|----|-----|-----|-----|-----|-----|
| mm | kg | mm | | mm | mm | mm | mm | mm | mm | mm | mm |
| 75 | 800 | 21 | M12 | 10 | x | x | x | x | x | | |
| 75 | 800 | 21 | M16 | 13 | | x | x | x | x | x | x |
| 75 | 800 | 21 | M20 | 15 | | x | x | x | x | x | x |
| 75 | 800 | 21 | M24 | 19 | | x | x | x | x | x | x |
| 75 | 800 | 21 | M30 | 24 | | | | | x | x | |
| 100 | 2000 | 36 | M12 | 10 | x | x | x | x | x | | |
| 100 | 2000 | 36 | M16 | 13 | | x | x | x | x | x | x |
| 100 | 2000 | 36 | M20 | 15 | | x | x | x | x | x | x |
| 100 | 2000 | 36 | M24 | 19 | | x | x | x | x | x | x |
| 100 | 2000 | 36 | M30 | 24 | | x | x | x | x | x | x |
| 125 | 3000 | 40 | M12 | 10 | x | x | x | x | x | | |
| 125 | 3000 | 40 | M16 | 13 | | x | x | x | x | x | x |
| 125 | 3000 | 40 | M20 | 15 | | x | x | x | x | x | x |
| 125 | 3000 | 40 | M24 | 19 | | x | x | x | x | x | x |
| 125 | 3000 | 40 | M30 | 24 | | x | x | x | x | x | x |

Ordering example

- Group + D + M + Thread Length ---> MFK 100 M16 x 100