



### Product Group MFHJ

Machine feet made of stainless steel with fixing holes, optional with antislip pad



#### Material

- Base body: AISI 304 (A2)
- Rubber: NBR 72 Shore



#### Product information

- The solid stainless steel design makes the foot highly resilient. The rounded shape makes cleaning easier.
- The machine foot can compensate for uneven floors up to 9°.
- The machine foot has two fixing holes
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The base is optionally available with a non-slip rubber plate that is firmly bonded to the stainless steel plate.
- Please order separately (MFHJxG, x = D)!

D	B	H1	H2	d	F max.	M	WAF		100	150	180	230
mm	mm	mm	mm	mm	kg		mm	mm	mm	mm	mm	mm
80	27	26	5	8,4	6000	M12	10		x	x	x	x
80	27	26	5	8,4	6000	M16	13		x	x	x	x
80	27	26	5	8,4	6000	M20	17		x	x	x	x
80	27	26	5	8,4	6000	M24	19		x	x	x	x
80	27	26	5	8,4	6000	M30	24		x	x	x	x
80												
90	32	26	5	13	6000	M12	10		x	x	x	x
90	32	26	5	13	6000	M16	13		x	x	x	x
90	32	26	5	13	6000	M20	17		x	x	x	x
90	32	26	5	13	6000	M24	19		x	x	x	x
90	32	26	5	13	6000	M30	24		x	x	x	x
90												
110	44	26	5	13	6000	M16	13		x	x	x	x
110	44	26	5	13	6000	M20	17		x	x	x	x
110	44	26	5	13	6000	M24	19		x	x	x	x
110	44	26	5	13	6000	M30	24		x	x	x	x
110												
150	62	26	5	16	6000	M16	13		x	x	x	x
150	62	26	5	16	6000	M20	17		x	x	x	x
150	62	26	5	16	6000	M24	19		x	x	x	x



# Walter Bethke GmbH & Co. KG

Technische Kunststoff - und Hybridprodukte

D	B	H1	H2	d	F max.	M	WAF	mm	100	150	180	230
mm	mm	mm	mm	mm	kg		mm		mm	mm	mm	mm
150	62	26	5	16	6000	M30	24		x	x	x	x
150	62	26	5	16	6000	M36	30		x	x	x	x
150												

## Ordering example

• Group + D + M + Thread Length ---> MFHJ 110 M16 x 100