



Product Group MFCF

Eccentric machine feet made of stainless steel with one fixing hole, optional with ant slip pad



Material

- Base body: AISI 304 (A2)
- Rubber: NBR 72 Shore



Product information

- The machine foot has its threaded spindle displaced from the centre of the foot plate which provides a larger distance between spindle and fixing hole.
- The solid stainless steel design makes the foot highly resilient. The rounded shape makes cleaning easier.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- The base is optionally available with a non-slip rubber plate that is firmly bonded to the stainless steel plate.
- Please order separately (MFCFxG, x = D)!

| Order Number | D | B | H1 | H2 | d | F max. | M | L | WAF |
|--------------------|-----|----|----|----|----|--------|-----|-----|-----|
| | mm | mm | mm | mm | mm | kg | | mm | mm |
| MFCF 110 / M16x100 | 110 | 70 | 14 | 5 | 13 | 6000 | M16 | 100 | 13 |
| MFCF 110 / M16x150 | 110 | 70 | 14 | 5 | 13 | 6000 | M16 | 150 | 13 |
| MFCF 110 / M16x180 | 110 | 70 | 14 | 5 | 13 | 6000 | M16 | 180 | 13 |
| MFCF 110 / M16x230 | 110 | 70 | 14 | 5 | 13 | 6000 | M16 | 230 | 13 |
| MFCF 110 / M20x100 | 110 | 70 | 14 | 5 | 13 | 6000 | M20 | 100 | 17 |
| MFCF 110 / M20x150 | 110 | 70 | 14 | 5 | 13 | 6000 | M20 | 150 | 17 |
| MFCF 110 / M20x180 | 110 | 70 | 14 | 5 | 13 | 6000 | M20 | 180 | 17 |
| MFCF 110 / M20x230 | 110 | 70 | 14 | 5 | 13 | 6000 | M20 | 230 | 17 |
| MFCF 110 / M24x100 | 110 | 70 | 14 | 5 | 13 | 6000 | M24 | 100 | 19 |
| MFCF 110 / M24x150 | 110 | 70 | 14 | 5 | 13 | 6000 | M24 | 150 | 19 |
| MFCF 110 / M24x180 | 110 | 70 | 14 | 5 | 13 | 6000 | M24 | 180 | 19 |
| MFCF 110 / M24x230 | 110 | 70 | 14 | 5 | 13 | 6000 | M24 | 230 | 19 |
| MFCF 110G | 110 | | | | | | | | |

Ordering example

- Group + D + M + Thread Length ---> MFCF 110 M16 x 100