


### Product Group JTHE

Adjustable feet made of PA with stainless steel cover and hexagonal adjusting screw, swivel base, for ground plates of group JTH BF/TPE/GP




#### Standard Colours

- black RAL 9005

#### Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Cover: Stainless Steel
- Base: Polyamide (PA)



#### Product information

- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- \* ) = Production with assembly aid Pozidriv 2 in the base (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

#### Product options on inquiry

- Further thread lengths/sizes
- Hexagon socket in thread end (please look at JTHE ISK)

| D  | F max. | H    | H1 | M   | WAF | 16 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 120 |
|----|--------|------|----|-----|-----|----|----|----|----|----|----|----|----|----|-----|-----|
| mm | kg     | mm   | mm |     | mm  | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm  | mm  |
| 38 | 400    | 13,5 | 20 | M8  | 13  | x  | x  | x  | x  | x  | x  | x  | x  | x  | x   | x   |
| 38 | 550    | 13,5 | 22 | M10 | 17  | x  | x  | x  | x  | x  | x  | x  | x  | x  | x   | x   |
| 38 | 650    | 13,5 | 24 | M12 | 19  |    |    | x  | x  | x  | x  | x  | x  | x  | x   | x   |
| 48 | 400    | 13,5 | 20 | M8  | 13  | x  | x  | x  | x  | x  | x  | x  | x  | x  | x   | x   |
| 48 | 550    | 13,5 | 22 | M10 | 17  | x  | x  | x  | x  | x  | x  | x  | x  | x  | x   | x   |
| 48 | 650    | 13,5 | 24 | M12 | 19  |    |    | x  | x  | x  | x  | x  | x  | x  | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ---> JTHE 38 M10x 60