




### Product Group JTM ISK

Adjustable feet made of galvanised steel with hexagonal adjusting screw and hexagon in the thread end, swivel base



#### Material

- Screw: DIN 558-4.6-A2F (zinc-plated)
- Base: zinc-plated steel



#### Product information

- B = with fixing holes
- The feet must be adjusted unloaded.
- The adjustable feet are not suitable as load gliders.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- B = with fixing holes
- As mounting aid Torx T20 in the plate (max. torque 3.4 Nm)
- The applicability for automated assembly will be examined by the customer. In the case of standard delivery, there is no guarantee of suitability for automated assembly (range of torque, tolerance limits of thread and more).

#### Product options on inquiry

- Further thread lengths/sizes
- Stainless steel metal base

D	F max.	A	d	H	H1	M	WAF	SW1	20	30	40	50	60	70	80	90	100
mm	kg	mm	mm	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
30	650			6	11,5	M8	13	4	x	x	x	x	x	x	x	x	x
30	650			6	12,5	M10	17	5	x	x	x	x	x	x	x	x	x
40	650			6	11,5	M8	13	4	x	x	x	x	x	x	x	x	x
40	650			6	12,5	M10	17	5	x	x	x	x	x	x	x	x	x
40	650	29	4	6	11,5	M8	13	4	x	x	x	x	x	x	x	x	x
40	650	29	4	6	12,5	M10	17	5	x	x	x	x	x	x	x	x	x
50	650			6	11,5	M8	13	4	x	x	x	x	x	x	x	x	x
50	650			6	12,5	M10	17	5	x	x	x	x	x	x	x	x	x
50	650	36	5	6	11,5	M8	13	4	x	x	x	x	x	x	x	x	x
50	650	36	5	6	12,5	M10	17	5	x	x	x	x	x	x	x	x	x

#### Ordering example

- Group + D + M + Thread Length ---> JTMB ISK 40 M10x 60