


Product Group MFEF

Machine feet made of glass fibre reinforced polyamide, zinced steel thread and vibration-damping rubber base





Standard Colours

- black

Material

- Thread: zinc-plated steel
- Base: glass fibre reinforced polyamide (PA-GF)
- Rubber: NBR 70 Shore



Product information

- A thicker rubber plate absorbs oscillations and vibrations.
- The machine foot can compensate for uneven floors up to 4°.
- There are two prepared screw-on holes (closed).
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Compressors, feeders, vibrators, cleaning machines
- The foot is used in work areas with low stress.
- The vulcanised polyamide base is used to solve vibration problems.

The base is made of vulcanised polyamide and is used to solve vibration problems.

Product options on inquiry

- Delivery with additional steel nut possible.

A	D	d	F max.	H	H1	H2	M	WAF	50	75	100	125	150	175	200	225	250
mm	mm	mm	kg	mm	mm	mm		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
56	83	8,5	2500	28	36	10	M14	16	x	x	x	x	x	x			
56	83	8,5	2500	28	36	10	M16	16	x	x	x	x	x	x	x		
56	83	8,5	2500	28	40	10	M20	17		x	x	x	x	x	x	x	
73	103	12,5	3500	33	45	10	M16	17	x	x	x	x	x	x	x	x	
73	103	12,5	3500	33	45	10	M20	17		x	x	x	x	x	x	x	
73	103	12,5	3500	33	47	10	M24	20		x	x	x	x	x	x	x	
87	123	12,5	4500	37	50	10	M16	20	x	x	x	x	x	x	x	x	
87	123	12,5	4500	37	50	10	M20	20		x	x	x	x	x	x	x	
87	123	12,5	4500	37	50	10	M24	20		x	x	x	x	x	x	x	x
87	123	12,5	4500	37	50	10	M30	26			x	x	x	x	x	x	x

Ordering example

- Group + D + M + Thread Length ---> MFEF 83 M14x 50