



### Product Group MFSSG

Machine feet made of stainless steel with fixing holes and antislip pad (A)



#### Material

- Base body: AISI 304 (A2)
- Antislip pad: NBR 70 Shore



#### Product information

- The antislip pad is supplied without holes.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.

#### Product options on inquiry

- Machine foot made of stainless steel AISI 316 (A4)
- Delivery with additional steel nut possible.

| A   | D   | d    | F max. | H  | H1 | M   | WAF | 100 | 150 | 200 | 250 |
|-----|-----|------|--------|----|----|-----|-----|-----|-----|-----|-----|
| mm  | mm  | mm   | kg     | mm | mm |     | mm  | mm  | mm  | mm  | mm  |
| 74  | 100 | 12,5 | 3500   | 20 | 33 | M16 | 20  | x   | x   | x   |     |
| 74  | 100 | 12,5 | 4000   | 20 | 33 | M20 | 20  | x   | x   | x   | x   |
| 74  | 100 | 12,5 | 4500   | 20 | 34 | M24 | 20  | x   | x   | x   | x   |
| 90  | 120 | 12,5 | 4500   | 22 | 35 | M20 | 20  | x   | x   | x   | x   |
| 90  | 120 | 12,5 | 5000   | 22 | 36 | M24 | 20  | x   | x   | x   | x   |
| 90  | 120 | 12,5 | 6000   | 22 | 36 | M30 | 26  | x   | x   | x   | x   |
| 122 | 159 | 12,5 | 5000   | 23 | 36 | M20 | 20  | x   | x   | x   | x   |
| 122 | 159 | 12,5 | 6000   | 23 | 37 | M24 | 20  | x   | x   | x   | x   |
| 122 | 159 | 12,5 | 7000   | 23 | 37 | M30 | 26  | x   | x   | x   | x   |

#### Ordering example

- Group + D + M + Thread Length ---> MFSSG 100 M16x 100 (A)