



### Product Group MFTV

Machine feet made of stainless steel with sealing bush and vulcanised rubber pad



#### Material

- Base body: AISI 304 (A2)
- Rubber: NBR 80 Shore, vulcanized



#### Product information

- The machine base has a sealing bush that covers parts of the thread. An O-ring is incorporated inside the bush. The sealing ring prevents the penetration of dirt by mechanically sticking to the thread surface. Thus the strictest legal hygiene standards are fulfilled.
- Die abgerundete Form und der verdeckte Übergang vom Fuß zum Gewinde erleichtern die Reinigung.
- EPDM meets the USDA standards for rubber products.
- The machine foot can compensate for uneven floors up to 10°.
- The load capacity of the screw (buckling length!) may be less than indicated in the table.
- Character dimension "L2" corresponds to the maximum usable stroke in mm.
- Especially suitable for tanks and cisterns, also for the beverage industry, chemical industry

Order Number	D	D1	F max.	H	H1	L	L1	L2	M	WAF	SW1
	mm	mm	kg	mm	mm	mm	mm	mm		mm	mm
MFTV 80 / M16x125	80	25	1000	25	38	125	60	40	M16	17	20
MFTV 80 / M16x150	80	25	1000	25	38	150	60	40	M16	17	20
MFTV 80 / M20x150	80	30	1000	25	38	150	60	40	M20	17	26
MFTV 100 / M16x150	100	25	1500	30	43	150	60	40	M16	17	20
MFTV 100 / M20x150	100	30	1500	30	43	150	60	40	M20	17	26
MFTV 100 / M24x150	100	35	1500	30	44	150	60	40	M24	20	30
MFTV 100 / M30x150	100	42	1500	30	44	150	60	40	M30	26	36
MFTV 120 / M16x150	120	25	3000	32	47	150	60	40	M16	17	20
MFTV 120 / M20x150	120	30	3000	32	47	150	60	40	M20	17	26
MFTV 120 / M24x150	120	35	3000	32	47	150	60	40	M24	20	30
MFTV 120 / M30x150	120	42	3000	32	49	150	60	40	M30	26	36