


### Product Group RJG

Adjusting plugs made of PA 6 for round tubes with slip stopper, one piece outer body and injection moulded thread





#### Standard Colours

- black RAL 9005

#### Material

- Polyamide 6 (PA 6)
- Anti-slip insert: Polyurethane (PUR)



• The feet must be adjusted in an unloaded state. • The specified axial, static load capacity refers to a screw turned out 10 mm and resting on the full surface. • Adjusting plugs are not suitable as load gliders. • Adjusting plugs are not suitable for dynamic load.

- \*) K = split assembled outer part
- \*\*) = The lamella shape of the nut can be closed or interrupted
- \*\*\*) = from  $\phi$  60 mm supplied with mounted threaded shell
- Please observe the material hints for polyamide (PA).

#### Product options on inquiry

- Further sizes
- Other special productions

Order Number	D	F max.	H	H1	L	L1	M	WAF	t
	mm	kg	mm	mm	mm	mm		mm	mm
RJG 25x1,5-2/M16x25/8k	25	150	5	5	19,7	22	M16	24	1,5-2
RJG 30x1-1,5/M22x25/8k	30	300	5	5	19,7	29	M22	28	1-1,5
RJG 30x1,5-2 K/M22x25/8k *	30	250	5	5	27	29	M22	28	1,5-2
RJG 32x1,5-2/M22x25/8k **	32	300	5	5	19,7	29	M22	28	1,5-2
RJG 35x1,5-2/M22x25/8k	35	300	5	5	29,3	29	M22	28	1,5-2
RJG 35x2-2,5/M22x25/8k	35	300	5	5	29,3	29	M22	28	2-2,5
RJG 38x1,5-2/M22x25/8k	38	300	5	5	29,3	29	M22	28	1,5-2
RJG 40x1,5-2/M22x25/8k **	40	300	5	5	29,3	29	M22	28	1,5-2
RJG 40x2-2,5/M22x25/8k **	40	300	5	5	29,3	29	M22	28	2-2,5
RJG 42x1,5-2/M30x30/8k	42	300	5	5	29,3	31	M30	41	1,5-2
RJG 45x1,5-2/M30x30/8k	45	300	5	5	29,3	31	M30	41	1,5-2
RJG 48x1,5-2/M30x30/8k	48	300	5	5	29,3	31	M30	41	1,5-2
RJG 50x1,5-2/M30x30/8k	50	300	5	5	29,3	31	M30	41	1,5-2
RJG 50,8x1,2-2/M30x30/8k	50	300	5	5	29,3	31	M30	41	1,2-2
RJG 60x1,5-2/S42x2x40/12k ***	60	300	6	10	34,7	40	S42x2	58	1,5-2
RJG 80x1,5-2/S56x2x40/12k ***	80	300	6	10	34,7	40	S56x2	74	1,5-2