


### Product Group RJG

Adjusting plugs made of PA 6 for round tubes with slip stopper, one piece outer body and injection moulded thread





#### Standard Colours

- black RAL 9005

#### Material

- Polyamide 6 (PA 6)
- Anti-slip insert: Polyurethane (PUR)



- The feet must be adjusted in an unloaded state.
- The specified axial, static load capacity refers to a screw turned out 10 mm and resting on the full surface.
- Adjusting plugs are not suitable as load gliders.
- Adjusting plugs are not suitable for dynamic load.

- \*) K = split assembled outer part
- \*\*) = The lamella shape of the nut can be closed or interrupted
- \*\*\*) = from  $\phi 60$  mm supplied with mounted threaded shell
- Please observe the material hints for polyamide (PA).

#### Product options on inquiry

- Further sizes
- Other special productions

| Order Number                  | D  | F max. | H  | H1 | L    | L1 | M     | WAF | t     |
|-------------------------------|----|--------|----|----|------|----|-------|-----|-------|
|                               | mm | kg     | mm | mm | mm   | mm |       | mm  | mm    |
| RJG 25x1,5-2/M16x25/8k        | 25 | 150    | 5  | 5  | 19,7 | 22 | M16   | 24  | 1,5-2 |
| RJG 30x1-1,5/M22x25/8k        | 30 | 300    | 5  | 5  | 19,7 | 29 | M22   | 28  | 1-1,5 |
| RJG 30x1,5-2 K/M22x25/8k *    | 30 | 250    | 5  | 5  | 27   | 29 | M22   | 28  | 1,5-2 |
| RJG 32x1,5-2/M22x25/8k **     | 32 | 300    | 5  | 5  | 19,7 | 29 | M22   | 28  | 1,5-2 |
| RJG 35x1,5-2/M22x25/8k        | 35 | 300    | 5  | 5  | 29,3 | 29 | M22   | 28  | 1,5-2 |
| RJG 35x2-2,5/M22x25/8k        | 35 | 300    | 5  | 5  | 29,3 | 29 | M22   | 28  | 2-2,5 |
| RJG 38x1,5-2/M22x25/8k        | 38 | 300    | 5  | 5  | 29,3 | 29 | M22   | 28  | 1,5-2 |
| RJG 40x1,5-2/M22x25/8k **     | 40 | 300    | 5  | 5  | 29,3 | 29 | M22   | 28  | 1,5-2 |
| RJG 40x2-2,5/M22x25/8k **     | 40 | 300    | 5  | 5  | 29,3 | 29 | M22   | 28  | 2-2,5 |
| RJG 42x1,5-2/M30x30/8k        | 42 | 300    | 5  | 5  | 29,3 | 31 | M30   | 41  | 1,5-2 |
| RJG 45x1,5-2/M30x30/8k        | 45 | 300    | 5  | 5  | 29,3 | 31 | M30   | 41  | 1,5-2 |
| RJG 48x1,5-2/M30x30/8k        | 48 | 300    | 5  | 5  | 29,3 | 31 | M30   | 41  | 1,5-2 |
| RJG 50x1,5-2/M30x30/8k        | 50 | 300    | 5  | 5  | 29,3 | 31 | M30   | 41  | 1,5-2 |
| RJG 50,8x1,2-2/M30x30/8k      | 50 | 300    | 5  | 5  | 29,3 | 31 | M30   | 41  | 1,2-2 |
| RJG 60x1,5-2/S42x2x40/12k *** | 60 | 300    | 6  | 10 | 34,7 | 40 | S42x2 | 58  | 1,5-2 |
| RJG 80x1,5-2/S56x2x40/12k *** | 80 | 300    | 6  | 10 | 34,7 | 40 | S56x2 | 74  | 1,5-2 |